200 SERIES NARROLINE[®] DOUBLE-HUNG WINDOWS



Table of Basic Unit Sizes Scale 1/8" = 1'-0" (1:96)

| Unit Dimension | 1'-9 ⁵ /8" 2'-1 ⁵ /8" (549) (651) | 2'-5 ⁵ /8" (752) | 2'-9 5/8" | 3'-1 ⁵ /8" (956) | 3'-5 ⁵ /8" (1057) | 3'-9 ⁵ /8" (1159) |
|--|---|--|-------------------------------|--------------------------------|---|---|
| Minimum | 1 ¹ 10 ¹ /8" 2 ¹ -2 ¹ /8" | 2'-6 1/8" | 2'-10 ¹ /8" | 3'-2 1/8" | 3'-6 1/8" | 3'-10 1/8" |
| Rough Opening | (562) (664) 16 ⁷ /16" 20 ⁷ /16" | (765) 24 ⁷ / ₁₆ " | (867) 28 ⁷ /16" | (968) 32 ⁷ /16" | (1070) 36 ⁷ / ₁₆ " | (1172) 40 ⁷ / ₁₆ " |
| Unobstructed Glass | (418) (519) | (621) | (722) | (824) | (926) | (1027) |
| 3'-1 1/4" (946) 3'-1 1/4" (946) 13 ¹⁵ /16" (354) | | | | | | |
| | 18210 20210 | 24210 | 28210 | 30210 | 34210 | 38210 |
| 3'-5 1/4" (1048) 3'-5 1/4" (1048) 15 15/16" (405) | | | | | | |
| | 1832 2032 | 2432 | 2832 | 3032 | 3432 | 3832 |
| 4'-1 ^{1/4} " (1251) 4'-1 ^{1/4} " (1251) 19 ^{15/16} " (506) | | | | | | |
| + + + | 18310 20310 | 24310 | 28310 | 30310 | 34310 | 38310 |
| 4'-5 1/4" (1353) 4'-5 1/4" (1353) 21 ¹⁵ /16" (557) | | | | | | |
| | 1842 2042 | 2442 | 2842 | 3042 | 3442 | 3842 |
| 4'-9 1/4" (1454) 4'-9 1/4" (1454) 23 15/16" (608) | | | | | | |
| | 1846 2046 | 2446 | 2846 | 3046 ♦ | 3446 ♦ | 3846 ♦ |
| 5'-5 1/4" (1657) 5'-5 1/4" (1657) 27 ¹⁵ /16" (710) | | | | | | |
| | 1852 2052 | 2452 | 2852 ♦ | 3052 • | 3452 ♦ | 3852 ♦ |
| 100 July 100 | | | | | | |
| 5'-9 1/4" (1759) 5'-9 1/4" (1759) 35 ¹⁵ /16" 23 ¹⁵ /16" (913) (608) | | | | | | |
| 5'-9 (17 5'-9 5'-9 (17 (17 (17 (17) (913) | | | | | | |
| 35 | 1856† 2056† | 2456† | 2856† | 3056†♦ | 3456†♦ | 3856†♦ |
| + + + | | 24301 | 28501 | 303014 | 34501 | 385014 |
| () () () () | | | | | | |
| 6'-5 1/4" (1962) 6'-5 1/4" (1962) (1962) 33 15/16" (862) | | | | | | |
| | | | | | | |
| | 1862* 2062* | 2462* | 2862*• | 3062*• | 3462*♦ | 3862*♦ |
| Divided Light Patterns for Narroline [®] Windows | | | | | | |
| In additon to the grille patterns shown in these tables, other standard and specified equal light patterns are available. Not all grille patterns are available in all configurations. | | | | | | |
| | | | | | | |
| * These units have restricted sash travel. These units meet or exceed the following dimensions: Clear Openable Area | | | | | | |
| "Cottage style" units and have unequal of 5.7 sq. ft., Clear Openable Width of 20" and Clear Openable Height of 24" Opening specifications will change with Performance Upgrades . | | | | | | |
| sash. The top sash is shorter than the of building wraps, flashing, sill panning, brackets, fasteners or other | | | | | | |
| bottom sash. Units items. with equal sash "Unabetrusted Clears" buidt measurement is far single cash only | | | | | | |
| by description. • "Unit Dimension" always refers to outside frame to frame dimension. | | | | | | |
| Contact supplier • Dimensions in parentheses are in millimeters. for lead times. • When ordering, be sure to specify color desired: White or Sandtone. | | | | | | |
| | | | | | | |

Light-colored areas are Andersen[®] parts included with the unit. Dark-colored areas are additional Andersen parts required to complete unit assembly as shown and must be specifically ordered.