

Andersen® VeriLock® Wireless Security Sensors – Spec Sheet

Technical information for: Security Providers and IT Technicians

Product Overview

Andersen® VeriLock® integrated security sensors are the only home security sensors that are integrated into the hardware of your windows and patio doors. These patented wireless sensors not only tell you if a window or patio door is open, they also tell you if they're unlocked*. No other sensor can do that.

Features & Benefits

- Integrated into the window and patio door hardware
- Open/Closed and Lock/Unlocked status*
- Easy replaceable Lithium coin cell battery
- Maintains the window or patio door limited warranty

Applications

200 Series

- Perma-Shield® Patio Door
- Narroline® Gliding Patio Door

400 Series

- Casement/Awning Window
- Double-Hung Window
- Woodwright® Double-Hung Window
- Frenchwood® Inswing Patio Doors
- Frenchwood® Outswing Patio Doors
- Frenchwood® Gliding Patio Doors

A-Series

- Casement/Awning Window
- Double-Hung Window
- Frenchwood® Hinged Inswing Patio Doors

- Frenchwood® Hinged Outswing Patio Doors
- Frenchwood® Gliding Patio Doors

E-Series

- Casement/Awning Window
- Push-Out Casement Window
- French Casement Window
- Double-Hung Window
- Gliding Window
- Inswing Hinged Patio Doors
- Outswing Hinged Patio Doors
- Gliding Patio Doors
- French Gliding Patio Doors
- Inswing Venting Sidelite
- Outswing Venting Sidelite

Technical Data:

Power Source

- 3V Lithium battery (supplied)

Transmit Frequency

- 345 MHz

Compatibility

- **Compatible with all Honeywell 5800 Series Wireless control panels**

Security Panel Requirements

- Each VeriLock sensor utilizes two loops and therefore two wireless zones.
 - Loop 1 is used to provide open/close notification
 - Loop 2 is used to provide lock/unlock notification

*When properly configured and maintained with a professionally installed security system and/or self-monitoring system compatible with Honeywell® 5800 sensors. See your dealer for more information.

Third Party Integrations

- Vendors
 - Control4®
 - Lutron RadioRa 2®
 - Savant Systems, LLC
 - Universal Remote Controls
 - Key Digital®
 - Crestron®
- Nexia™ Home Intelligence
- Wink

Requires the use of Honeywell connected building module 4232CBM and VISTA™ series security panel.

Requires the use of Andersen® Translator. (PN 9142223)

Agency Listings

- FCC
- IC
- cETLus

Warranty

- Two year limited warranty

How to Order

- Your local Andersen® dealer
- The Home Depot®
- Andersen® Parts Store
<https://parts.andersenwindows.com>

Related Publications

- General Information:
<https://www.andersenwindows.com/connect>
- Third party integrations:
<https://security.honeywell.com/hsc/solutions/integration/index.html>
<http://www.nexiahome.com/>
<http://www.wink.com/>

Technical Support

- Contact Andersen® Customer Service: 855-337-8806
- Please visit
<https://www.andersenwindows.com/connect>

All marks where denoted are trademarks of their respective owners.
©2016 Andersen Corporation. All rights reserved.